

PRODUCT SPEC SHEET

Mohawk RealSound™

The only true patented underlayment system on the market

- Pre-attached moisture barrier helps protect floors from moisture damage
- Helps reduce hollow sounds
- Mold and mildew resistant
- Easy to install with attached lip and tape system
- Safe for under floor heating
- Self-leveling
- Odorless
- Warranty is the same as your Mohawk floor

Product Information

Name	RealSound
Style Number	LU10A
Universal Product Code	8-16366-39106-1
Dimensions - Standard	40" W x 30' L x .08" Thickness
Dimensions - Metric	1.02 m x 9.14 m x 2 mm
Net Weight Per Roll - LBS	2.25
Lip & Tape	Yes
Lip Size - inches	3
Sq Ft per roll	100
Rolls Per Box	30
Boxes per Pallet	1
Pallets Per Truck	78
Rolls Per Full Truckload	2340

Product Specifications

Material	Polypropylene Foam
Foam Color	Cinnamon Red
Film Color	Clear - 30% recycled content
Sound Transmission Class (STC)	66
Impact Insulation Class (IIC)	68
Foam Density (lbs/ft ³)	2
Thickness	2 mm
Moisture Barrier	1 mil
Chemical Resistance	Very Good
Water Absorption (lbs./sq.ft ²)	0.09
Water Vapor Transmission Rating	0.05
R Value	1.4
Compression Strength (psi)	3.33
Mold and Mildew Resistant	YES